

APPENDIX A Revision A	TRAILER MOUNTED SUPPORT SYSTEM PRODUCT DATA SHEET	
Company	DHS Systems LLC	
Part Number or NSN	1006178	DRASH Model HP-2C/8E, Desert Tan
Specifications as applicable		
Safety and Mobility Certification by Military Test Center		
Trailer	l	
Stowage Components included with trailer	NA	
Cargo Volume Stowage, For shelter and accessory components In cubic feet	145 cu. ft.	
Physical Dimensions for trailer	6.75 ft H	
Height	7.2 ft W	
Width	16.2 ft L	
Length		
Recommended Prime Mover Vehicle	нммуу	Requires a vehicle capable of towing a 4,200 lb. trailer.
Empty GVW	2,382 lb.	
Tongue Weight	250 lb.	
Tire Type and Size	Radial	Two 37 x 12.50 x 16.5 LT Goodyear Wrangler R/T II, Load Rating C bias-ply, run-flat tires.
Fuel Tank Capacity	5 gal.	
Generator	•	
Nominal Output in kW, Volts AC, Hertz, Phase	NA	
Operating Environment	NA	
Enginetype	NA	
Fuel Type	NA	

First Ossassins of San		
Fuel Consumption	NA	
(AC Compressor On)	1.0.	
At 25% load		
At 50% Load		
At 75% Load		
at maximum output		
Noise in DB at 25 feet		
(AC Compressor On)	NA	
At 25% load		
At 50% load		
At 75% Load		
At maximum rated load		
Heater		
Tealer		
Nominal Output in BTU's		
	NA	
Electric Requirement		
Volts/Amps		
Air Conditioning		
Maximum Cooling Capacityin		00 000 DTIV
BTU's		96,000 BTU/hr
Maximum Heat Output	2 stoge has	92,000 BTU/hr electric heat
Capacity in BTU's	2 Stage Hea	192,000 B TO/III electric fleat
RefrigerantType		
	R407-C	
<u> </u>		
CFM Air Flow		
	3,000	
Min Donat Diamatan		
Air Duct Diameter		Two 44 in Comply Two 44 in Detum
	4 Ducts	Two 14 in Supply Two 14 in Return
Power Requirements in kW, VAC, HZ,		
Phase	28kW	
Filase		200) (4 0 20 11 - 2 :: h
1		208 VAC, 60 Hz, 3-phase.
Special/Additional Features:		
poolain aditional rodition.	The HP-2C/8E Trailer provides two primary features for the end user of a smaller	
	DRASH shelter - cargo space and environmental control. It has a 145	
		argo area, includes a 5 gallon fuel tank and comes with an 8 Ton
	ECU.	argo area, includes a 5 gallori fuel tarik and cornes with an 6 for
	ECU.	
	INCLUDES	:
	1 Drip Berm(T295188) 1 Supply Duct(T291230) 1 Return Duct(T291432)	
	i Fire Extin	guisher, 5lbs, (P/N T295175), Qty. = 1

ه

(